

CA2-*(**) U-BOLT CLAMPS

U-bolt clamps (with angled steel) (for metric series pipe)

Series No.	Nominal caliber	350°C max load	d	B	C	D	E	F	G
CA2-1 (15)	15	4710	M8	70	28	35	35	30	L50X50X6
CA2-1 (20)	20			80	37	40	38		
CA2-1 (25)	25			85	43	45	40		
CA2-1 (32)	32	7460	M10	95	54	55	45	30	L50X50X6
CA2-1 (40)	40			100	60	55			
CA2-1 (50)	50			115	72	60			
CA2-1 (65)	65	10990	M12	130	88	75	55	30	L50X50X6
CA2-1 (80)	80			145	104	80			
CA2-1 (100)	100			170	130	95			
CA2-1 (125)	125	20600	M16	215	160	115	70	35	L63X63X6
CA2-1 (150)	150			250	188	130			
CA2-1 (200)	200			300	239	155			
CA2-1 (250)	250	32180	M20	370	297	185	80	45	L80X80X10
CA2-1 (300)	300	46300	M24	450	353	220	90	55	L100X100X10

1.The clamp surface is zinc plated. Different treatments upon request

2.Other materials and pipe o.d. upon request

Different forms or requirements upon request

Note: acc. to national standard: **JB/ZQ4008-97**